



# Single-ended Capacitors

**Series/Type: B41898**

The following products presented in this data sheet are being withdrawn.

Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B41898A7477M008		2021-05-28	2021-11-30	2022-03-01
B41898A7477M004		2021-05-28	2021-11-30	2022-03-01
B41898A7477M002		2021-05-28	2021-11-30	2022-03-01



Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B41898A7477M001		2021-05-28	2021-11-30	2022-03-01
B41898A7477M000		2021-05-28	2021-11-30	2022-03-01
B41898A7278M012		2021-05-28	2021-11-30	2022-03-01
B41898A7278M003		2021-05-28	2021-11-30	2022-03-01
B41898A7278M002		2021-05-28	2021-11-30	2022-03-01
B41898A7278M001		2021-05-28	2021-11-30	2022-03-01
B41898A7278M000		2021-05-28	2021-11-30	2022-03-01
B41898A7228M012		2021-05-28	2021-11-30	2022-03-01
B41898A7228M004		2021-05-28	2021-11-30	2022-03-01
B41898A7228M003		2021-05-28	2021-11-30	2022-03-01
B41898A7228M002		2021-05-28	2021-11-30	2022-03-01
B41898A7228M001		2021-05-28	2021-11-30	2022-03-01
B41898A7228M000		2021-05-28	2021-11-30	2022-03-01
B41898A7188M012		2021-05-28	2021-11-30	2022-03-01
B41898A7188M009		2021-05-28	2021-11-30	2022-03-01
B41898A7188M004		2021-05-28	2021-11-30	2022-03-01
B41898A7188M003		2021-05-28	2021-11-30	2022-03-01
B41898A7188M002		2021-05-28	2021-11-30	2022-03-01
B41898A7188M001		2021-05-28	2021-11-30	2022-03-01
B41898A7188M000		2021-05-28	2021-11-30	2022-03-01
B41898A7158M012		2021-05-28	2021-11-30	2022-03-01
B41898A7158M009		2021-05-28	2021-11-30	2022-03-01
B41898A7158M004		2021-05-28	2021-11-30	2022-03-01
B41898A7158M003		2021-05-28	2021-11-30	2022-03-01
B41898A7158M002		2021-05-28	2021-11-30	2022-03-01
B41898A7158M001		2021-05-28	2021-11-30	2022-03-01
B41898A7158M000		2021-05-28	2021-11-30	2022-03-01
B41898A7108M012		2021-05-28	2021-11-30	2022-03-01
B41898A7108M009		2021-05-28	2021-11-30	2022-03-01
B41898A7108M004		2021-05-28	2021-11-30	2022-03-01
B41898A7108M003		2021-05-28	2021-11-30	2022-03-01
B41898A7108M002		2021-05-28	2021-11-30	2022-03-01
B41898A7108M001		2021-05-28	2021-11-30	2022-03-01
B41898A7108M000		2021-05-28	2021-11-30	2022-03-01
B41898A6687M012		2021-05-28	2021-11-30	2022-03-01
B41898A6687M009		2021-05-28	2021-11-30	2022-03-01
B41898A6687M004		2021-05-28	2021-11-30	2022-03-01
B41898A6687M003		2021-05-28	2021-11-30	2022-03-01



Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B41898A6687M002		2021-05-28	2021-11-30	2022-03-01
B41898A6687M001		2021-05-28	2021-11-30	2022-03-01
B41898A6687M000		2021-05-28	2021-11-30	2022-03-01
B41898A6477M008		2021-05-28	2021-11-30	2022-03-01
B41898A6477M004		2021-05-28	2021-11-30	2022-03-01
B41898A6477M002		2021-05-28	2021-11-30	2022-03-01
B41898A6477M001		2021-05-28	2021-11-30	2022-03-01
B41898A6477M000		2021-05-28	2021-11-30	2022-03-01
B41898A6337M008		2021-05-28	2021-11-30	2022-03-01
B41898A6337M004		2021-05-28	2021-11-30	2022-03-01
B41898A6337M002		2021-05-28	2021-11-30	2022-03-01
B41898A6337M001		2021-05-28	2021-11-30	2022-03-01
B41898A6337M000		2021-05-28	2021-11-30	2022-03-01
B41898A6188M012		2021-05-28	2021-11-30	2022-03-01
B41898A6188M003		2021-05-28	2021-11-30	2022-03-01
B41898A6188M002		2021-05-28	2021-11-30	2022-03-01
B41898A6188M001		2021-05-28	2021-11-30	2022-03-01
B41898A6188M000		2021-05-28	2021-11-30	2022-03-01
B41898A6158M012		2021-05-28	2021-11-30	2022-03-01
B41898A6158M004		2021-05-28	2021-11-30	2022-03-01
B41898A6158M003		2021-05-28	2021-11-30	2022-03-01
B41898A6158M002		2021-05-28	2021-11-30	2022-03-01
B41898A6158M001		2021-05-28	2021-11-30	2022-03-01
B41898A6158M000		2021-05-28	2021-11-30	2022-03-01
B41898A6108M012		2021-05-28	2021-11-30	2022-03-01
B41898A6108M009		2021-05-28	2021-11-30	2022-03-01
B41898A6108M004		2021-05-28	2021-11-30	2022-03-01
B41898A6108M003		2021-05-28	2021-11-30	2022-03-01
B41898A6108M002		2021-05-28	2021-11-30	2022-03-01
B41898A6108M001		2021-05-28	2021-11-30	2022-03-01
B41898A6108M000		2021-05-28	2021-11-30	2022-03-01
B41898A5478M012		2021-05-28	2021-11-30	2022-03-01
B41898A5478M003		2021-05-28	2021-11-30	2022-03-01
B41898A5478M002		2021-05-28	2021-11-30	2022-03-01
B41898A5478M001		2021-05-28	2021-11-30	2022-03-01
B41898A5478M000		2021-05-28	2021-11-30	2022-03-01
B41898A5338M012		2021-05-28	2021-11-30	2022-03-01
B41898A5338M009		2021-05-28	2021-11-30	2022-03-01



Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B41898A5338M004		2021-05-28	2021-11-30	2022-03-01
B41898A5338M003		2021-05-28	2021-11-30	2022-03-01
B41898A5338M002		2021-05-28	2021-11-30	2022-03-01
B41898A5338M001		2021-05-28	2021-11-30	2022-03-01
B41898A5338M000		2021-05-28	2021-11-30	2022-03-01
B41898A5278M012		2021-05-28	2021-11-30	2022-03-01
B41898A5278M004		2021-05-28	2021-11-30	2022-03-01
B41898A5278M003		2021-05-28	2021-11-30	2022-03-01
B41898A5278M002		2021-05-28	2021-11-30	2022-03-01
B41898A5278M001		2021-05-28	2021-11-30	2022-03-01
B41898A5278M000		2021-05-28	2021-11-30	2022-03-01
B41898A5228M012		2021-05-28	2021-11-30	2022-03-01
B41898A5228M009		2021-05-28	2021-11-30	2022-03-01
B41898A5228M004		2021-05-28	2021-11-30	2022-03-01
B41898A5228M003		2021-05-28	2021-11-30	2022-03-01
B41898A5228M002		2021-05-28	2021-11-30	2022-03-01
B41898A5228M001		2021-05-28	2021-11-30	2022-03-01
B41898A5228M000		2021-05-28	2021-11-30	2022-03-01
B41898A5188M012		2021-05-28	2021-11-30	2022-03-01
B41898A5188M009		2021-05-28	2021-11-30	2022-03-01
B41898A5188M004		2021-05-28	2021-11-30	2022-03-01
B41898A5188M003		2021-05-28	2021-11-30	2022-03-01
B41898A5188M002		2021-05-28	2021-11-30	2022-03-01
B41898A5188M001		2021-05-28	2021-11-30	2022-03-01
B41898A5188M000		2021-05-28	2021-11-30	2022-03-01
B41898A5158M012		2021-05-28	2021-11-30	2022-03-01
B41898A5158M009		2021-05-28	2021-11-30	2022-03-01
B41898A5158M004		2021-05-28	2021-11-30	2022-03-01
B41898A5158M003		2021-05-28	2021-11-30	2022-03-01
B41898A5158M002		2021-05-28	2021-11-30	2022-03-01
B41898A5158M001		2021-05-28	2021-11-30	2022-03-01
B41898A5158M000		2021-05-28	2021-11-30	2022-03-01
B41898A5108M008		2021-05-28	2021-11-30	2022-03-01
B41898A5108M004		2021-05-28	2021-11-30	2022-03-01
B41898A5108M002		2021-05-28	2021-11-30	2022-03-01
B41898A5108M001		2021-05-28	2021-11-30	2022-03-01
B41898A5108M000		2021-05-28	2021-11-30	2022-03-01
B41898A4478M012		2021-05-28	2021-11-30	2022-03-01



Ordering Code	Substitute Product	Date of Withdrawal	Deadline Last Orders	Last Shipments
B41898A4478M009		2021-05-28	2021-11-30	2022-03-01
B41898A4478M004		2021-05-28	2021-11-30	2022-03-01
B41898A4478M003		2021-05-28	2021-11-30	2022-03-01
B41898A4478M002		2021-05-28	2021-11-30	2022-03-01
B41898A4478M001		2021-05-28	2021-11-30	2022-03-01
B41898A4478M000		2021-05-28	2021-11-30	2022-03-01
B41898A4338M012		2021-05-28	2021-11-30	2022-03-01
B41898A4338M009		2021-05-28	2021-11-30	2022-03-01
B41898A4338M004		2021-05-28	2021-11-30	2022-03-01
B41898A4338M003		2021-05-28	2021-11-30	2022-03-01
B41898A4338M002		2021-05-28	2021-11-30	2022-03-01
B41898A4338M001		2021-05-28	2021-11-30	2022-03-01
B41898A4338M000		2021-05-28	2021-11-30	2022-03-01
B41898A4228M012		2021-05-28	2021-11-30	2022-03-01
B41898A4228M009		2021-05-28	2021-11-30	2022-03-01
B41898A4228M004		2021-05-28	2021-11-30	2022-03-01
B41898A4228M003		2021-05-28	2021-11-30	2022-03-01
B41898A4228M002		2021-05-28	2021-11-30	2022-03-01
B41898A4228M001		2021-05-28	2021-11-30	2022-03-01
B41898A4228M000		2021-05-28	2021-11-30	2022-03-01
B41898A4158M008		2021-05-28	2021-11-30	2022-03-01
B41898A4158M004		2021-05-28	2021-11-30	2022-03-01
B41898A4158M002		2021-05-28	2021-11-30	2022-03-01
B41898A4158M001		2021-05-28	2021-11-30	2022-03-01
B41898A4158M000		2021-05-28	2021-11-30	2022-03-01
B41898A4108M008		2021-05-28	2021-11-30	2022-03-01
B41898A4108M004		2021-05-28	2021-11-30	2022-03-01
B41898A4108M002		2021-05-28	2021-11-30	2022-03-01
B41898A4108M001		2021-05-28	2021-11-30	2022-03-01
B41898A4108M000		2021-05-28	2021-11-30	2022-03-01

Please contact your nearest TDK sales office if you need support in selecting a suitable substitute. The addresses of our worldwide sales network are presented at [www.tdk-electronics.tdk.com/sales](http://www.tdk-electronics.tdk.com/sales).

## Long-life grade capacitors

### Applications

- Automotive electronics

### Features

- Very long useful life
- High operating temperature capability
- High ripple current capability
- Low ESR
- RoHS-compatible

### Construction


- Radial leads
- Charge-discharge proof, polar
- Coated aluminum case
- Plus pole marking on the case side
- Case with safety vent

### Delivery mode

Terminal configurations and packing:

- Bulk
- Taped, Ammo pack
- Cut
- Kinked
- PAPR (Protection Against Polarity Reversal):  
crimped leads, J leads, bent leads

Refer to chapter "Single-ended capacitors – Taping, packing and lead configurations" for further details.




**Specifications and characteristics in brief**

Rated voltage $V_R$	16 ... 50 V DC				
Surge voltage $V_S$	$1.15 \cdot V_R$				
Rated capacitance $C_R$	330 ... 4700 $\mu\text{F}$				
Capacitance tolerance	$\pm 20\% \triangleq M$				
Dissipation factor $\tan \delta$ (20 °C, 120 Hz)	For capacitance higher than 1000 $\mu\text{F}$ add 0.02 for every increase of 1000 $\mu\text{F}$ .				
	$V_R$ (V DC)	16	25	35	50
	$\tan \delta$ (max.)	0.16	0.14	0.12	0.10
Leakage current $I_{\text{leak}}$ (20 °C, 5 min)	$I_{\text{leak}} = 0.01 \mu\text{A} \cdot \left( \frac{C_R}{\mu\text{F}} \cdot \frac{V_R}{V} \right)$ or 3 $\mu\text{A}$ , whichever is greater				
Self-inductance ESL	Diameter (mm)	12.5	16	18	
	ESL (nH)	20	26	34	
Useful life <sup>1)</sup> 125 °C; $V_R$ ; $I_{AC,R}$	> 7000 for $l \leq 25$ mm > 10000 h for $l > 25$ mm	Requirements: $ \Delta C/C  \leq 35\%$ of initial value $\tan \delta \leq 3$ times initial specified limit $I_{\text{leak}} \leq$ initial specified limit			
Voltage endurance test 125 °C, $V_R$	7000 for $l \leq 25$ mm 10000 h for $l > 25$ mm	Post test requirements: $ \Delta C/C  \leq 30\%$ of initial value $\tan \delta \leq 3$ times initial specified limit $I_{\text{leak}} \leq$ initial specified limit			
Vibration resistance test	To IEC 60068-2-6, test Fc: Frequency range 10 Hz ... 2 kHz, displacement amplitude max. 1.5 mm, acceleration max. 20 g, duration $3 \times 2$ h. Capacitor rigidly clamped by the aluminum case e.g. using our standard fixture				
IEC climatic category	To IEC 60068-1: 40/125/56 (–40 °C/+125 °C/56 days damp heat test)				
Sectional specification	IEC 60384-4				
Reference standard	AEC-Q200 <sup>2)</sup>				

1) Refer to chapter "General technical information, 5 Useful life" on how to interpret useful life.

2) Refer to chapter "General technical information, 2.3 AEC-Q200 standard" for further details.




**B41898**

**Very long useful life – 125 °C**

### Dimensional drawing

#### With stand-off rubber seal

Diameters (mm): 12.5, 16, 18



### Dimensions and weights

Dimensions (mm)				Approx. weight
d +0.5	l	a ±0.5	b	g
12.5	20 +2.0	5.0	0.60 ±0.05	3.6
12.5	25 +2.0	5.0	0.60 ±0.05	4.5
16	25 +2.0	7.5	0.80 ±0.05	7.5
16	31.5 +2.0	7.5	0.80 ±0.05	7.8
16	35.5 +2.0	7.5	0.80 ±0.05	9.2
18	20 +2.0	7.5	0.80 ±0.1	8.0
18	31.5 +2.0	7.5	0.80 ±0.1	11.0
18	35 +2.0	7.5	0.80 ±0.1	13.0
18	40 +2.5	7.5	0.80 ±0.1	16.0





### Overview of available types

Other voltage and capacitance ratings are available upon request.

$V_R$ (V DC)	16	25	35	50
	Case dimensions $d \times l$ (mm)			
$C_R$ ( $\mu\text{F}$ )				
330				12.5 × 20
470			12.5 × 20	12.5 × 25
680				16 × 25
1000	12.5 × 20	12.5 × 25	16 × 25	16 × 31.5
1500	12.5 × 25	16 × 25	16 × 31.5	18 × 35
1800		18 × 20	18 × 31.5	18 × 40
2200	16 × 25	16 × 31.5	18 × 35	
2700		16 × 35.5	18 × 40	
3300	16 × 31.5	18 × 31.5		
4700	18 × 31.5	18 × 40		


**B41898**
**Very long useful life – 125 °C**
**Technical data and ordering codes**

$C_R$ 120 Hz 20 °C $\mu\text{F}$	Case dimensions $d \times l$ mm	$\text{ESR}_{\text{max}}$ 10 kHz –40 °C $\Omega$	$\text{ESR}_{\text{max}}$ 10 kHz 20 °C $\Omega$	$Z_{\text{max}}$ 100 kHz 20 °C $\Omega$	$I_{\text{AC,R}}$ 100 kHz 125 °C mA	Ordering code (composition see below)
<b><math>V_R = 16 \text{ V DC}</math></b>						
1000	12.5 × 20	0.424	0.053	0.050	1490	B41898A4108M***
1500	12.5 × 25	0.352	0.044	0.042	1750	B41898A4158M***
2200	16 × 25	0.248	0.031	0.030	2300	B41898A4228M***
3300	16 × 31.5	0.192	0.024	0.023	2710	B41898A4338M***
4700	18 × 31.5	0.176	0.022	0.021	3270	B41898A4478M***
<b><math>V_R = 25 \text{ V DC}</math></b>						
1000	12.5 × 25	0.352	0.044	0.042	1750	B41898A5108M***
1500	16 × 25	0.248	0.031	0.030	2300	B41898A5158M***
1800	18 × 20	0.320	0.040	0.038	2100	B41898A5188M***
2200	16 × 31.5	0.192	0.024	0.023	2710	B41898A5228M***
2700	16 × 35.5	0.168	0.021	0.020	3050	B41898A5278M***
3300	18 × 31.5	0.176	0.022	0.021	3270	B41898A5338M***
4700	18 × 40	0.152	0.019	0.018	3900	B41898A5478M***
<b><math>V_R = 35 \text{ V DC}</math></b>						
470	12.5 × 20	0.488	0.061	0.058	1490	B41898A7477M***
1000	16 × 25	0.264	0.033	0.031	2300	B41898A7108M***
1500	16 × 31.5	0.232	0.029	0.028	2710	B41898A7158M***
1800	18 × 31.5	0.216	0.027	0.026	3270	B41898A7188M***
2200	18 × 35	0.208	0.026	0.025	3600	B41898A7228M***
2700	18 × 40	0.184	0.023	0.022	3900	B41898A7278M***
<b><math>V_R = 50 \text{ V DC}</math></b>						
330	12.5 × 20	0.651	0.074	0.070	1330	B41898A6337M***
470	12.5 × 25	0.510	0.058	0.055	1650	B41898A6477M***
680	16 × 25	0.352	0.040	0.038	2010	B41898A6687M***
1000	16 × 31.5	0.282	0.032	0.031	2430	B41898A6108M***
1500	18 × 35	0.255	0.029	0.028	2790	B41898A6158M***
1800	18 × 40	0.229	0.026	0.025	3400	B41898A6188M***

**Composition of ordering code**

\*\*\* = Version

000 = for standard leads, bulk

001 = for kinked leads, bulk

002 = for cut leads, bulk

 003 = for crimped leads, blister (for  $\varnothing$  16 ... 18 mm)

 004 = for J leads, blister (for  $\varnothing$  12.5 ... 16 mm and  $d \times l = 18 \times 20 \dots 18 \times 35$  mm)

 008 = for taped leads, Ammo pack, lead spacing  $F = 5.0$  mm (for  $\varnothing$  12.5 mm)

 009 = for taped leads, Ammo pack, lead spacing  $F = 7.5$  mm (for  $d \times l = 16 \times 25 \dots 16 \times 31.5$  mm and  $d \times l = 18 \times 20 \dots 18 \times 31.5$  mm)

 012 = for bent 90° leads, blister (for  $\varnothing$  16 ... 18 mm)




**B41898**

**Very long useful life – 125 °C**

**Useful life<sup>1)</sup>**

depending on ambient temperature  $T_A$  under ripple current operating conditions


$l \leq 25$  mm




**Useful life<sup>1)</sup>**

depending on ambient temperature  $T_A$  under ripple current operating conditions

$l > 25$  mm




1) Refer to chapter "General technical information, 5 Useful life" on how to interpret useful life.



**B41898**

**Very long useful life – 125 °C**

**Frequency factor of permissible ripple current  $I_{AC}$  versus frequency  $f$**





### Taping

Single-ended capacitors are available taped in Ammo pack from diameter 8 to 18 mm as follows:

Lead spacing  $F = 3.5 \text{ mm}$  ( $\varnothing d = 8 \text{ mm}$ )


Lead spacing  $F = 5.0 \text{ mm}$  ( $\varnothing d = 8 \dots 12.5 \text{ mm}$ )

Lead spacing  $F = 7.5 \text{ mm}$  ( $\varnothing d = 16 \dots 18 \text{ mm}$ ).

The dimensions for  $F$ ,  $P_1$  and  $1 \text{ max.}$  are specified with reference to the center of the terminal wires.

#### Lead spacing 3.5 mm ( $\varnothing d = 8 \text{ mm}$ )

Last 3 digits of ordering code: 006



KAL1447-V-E

#### Dimensions in mm

$\varnothing d$	F	H	W	$W_0$	$W_1$	$W_2$	P	$P_0$	$P_1$	$l_1$	t	$\Delta h$	$D_0$
8	3.5	18.5	18.0	9.5	9.0	3.0	12.7	12.7	4.6	1.0	0.7	1.0	4.0
Tolerance	+0.8 -0.2	$\pm 1.0$	$\pm 0.5$	min.	$\pm 0.5$	max.	$\pm 1.0$	$\pm 0.3$	$\pm 0.6$	max.	$\pm 0.2$	max.	$\pm 0.2$

Leads can also run straight through the taping area.




**B41898**

**Very long useful life – 125 °C**


**Lead spacing 5.0 mm (∅ d = 8 mm)**

Last 3 digits of ordering code: 008



**Lead spacing 5.0 mm (∅ d = 10 ... 12.5 mm)**

Last 3 digits of ordering code: 008




**Dimensions in mm**

∅ d	F	H	W	W <sub>0</sub>	W <sub>1</sub>	W <sub>2</sub>	H <sub>0</sub>	P	P <sub>0</sub>	P <sub>1</sub>	l <sub>1</sub>	t	∆h	D <sub>0</sub>
8		20.0		9.5			16.0	12.7	12.7	3.85				
10	5.0	19.0	18.0	9.5	9.0	1.5	—	12.7	12.7	3.85	1.0	0.6	1.0	4.0
12.5		19.0		11.5			—	15.0	15.0	5.0				
Tolerance	+0.8 -0.2	±0.75	±0.5	min.	±0.5	max.	±0.5	±1.0	±0.2	±0.5	max.	+0.3 -0.2	max.	±0.2

Taping is available up to dimensions d × l = 12.5 × 25 mm.


**Lead spacing 7.5 mm (∅ d = 16 ...18 mm)**

Last 3 digits of ordering code: 009


**Dimensions in mm**

∅ d	F	H	W	W <sub>0</sub>	W <sub>1</sub>	W <sub>2</sub>	P	P <sub>0</sub>	P <sub>1</sub>	l <sub>1</sub>	t	ΔP	Δh	D <sub>0</sub>
16	7.5	18.5	18.0	12.5	9.0	1.5	30.0	15.0	3.75	1.0	0.7	0	0	4.0
18														
Tolerance	±0.8	-0.5 +0.75	±0.5	min.	±0.5	max.	±1.0	±0.2	±0.5	max.	±0.2	±1.0	±1.0	±0.2

Taping is available up to dimensions d × l = 16 × 31.5 mm and 18 × 31.5 mm.



**B41898**

**Very long useful life – 125 °C**


### Cut or kinked leads

Single-ended capacitors are available with cut or kinked leads. Other lead configurations also available upon request.

### Cut leads


Last 3 digits of ordering code: 002

#### With stand-off rubber seal



KAL1085-I

#### With flat rubber seal



KAL1086-R

Case size d × l (mm)	Dimensions (mm) a ±0.5
10 × 12.5	5.0
10 × 16	5.0
10 × 20	5.0
12.5 × 20	5.0
12.5 × 25	5.0
16 × 20	7.5
16 × 25	7.5
16 × 31.5	7.5
16 × 35.5	7.5
16 × 40	7.5
18 × 20	7.5
18 × 25	7.5
18 × 31.5	7.5
18 × 35	7.5
18 × 40	7.5







### Kinked leads

Last 3 digits of ordering code: 001

#### With stand-off rubber seal




KAL1081-K




KAL1083-2

#### With flat rubber seal



KAL1082-T



KAL1084-A

Case size d × l (mm)	Dimensions (mm) a ±0.5
10 × 20	5.0
12.5 × 20	5.0
12.5 × 25	5.0
16 × 20	7.5
16 × 25	7.5
16 × 31.5	7.5
16 × 35.5	7.5
18 × 20	7.5
18 × 25	7.5
18 × 31.5	7.5
18 × 35	7.5
18 × 40	7.5



**B41898**

**Very long useful life – 125 °C**

**PAPR leads (Protection Against Polarity Reversal)**


These lead configurations ensure correct placement of the capacitor on the PCB with regard to polarity. PAPR leads are available for diameters from 10 mm up to 18 mm.

There are three configurations available: Crimped leads, J leads, bent 90° leads.

**Crimped leads**


Last 3 digits of ordering code: 003

**With stand-off rubber seal**



The series B41897 and B41898 have no sleeve nor minus pole marking, the positive pole is marked on the aluminum case side instead.



**Suggestion for PCB hole diameter**



Case size d × l (mm)	Dimensions (mm)					
	B ±0.2	C ±0.5	D ±0.1	E ±0.1	a ±0.5	Øb
16 × 20	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 × 25	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 × 31.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
16 × 35.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.05
18 × 20	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 × 25	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 × 31.5	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 × 35	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1
18 × 40	1.5	3.0	1.3	0.3	7.5	0.8 ±0.1


**J leads**


Last 3 digits of ordering code: 004




The series B41897 and B41898 have no sleeve nor minus pole marking, the positive pole is marked on the aluminum case side instead.

KAL1091-S-E

**Suggestion for PCB hole diameter**

 Suggestion for PCB hole diameter, wire  $\varnothing 0.6$  mm


KAL1092-1-E

 Suggestion for PCB hole diameter, wire  $\varnothing 0.8$  mm


KAL1093-9-E

Case size $d \times l$ (mm)	Dimensions (mm)				
	$C \pm 0.5$	$E \pm 0.5$	$J \pm 0.2$	$a \pm 0.5$	$\varnothing b$
10 × 12.5	3.2	0.7	1.2	5.0	$0.6 \pm 0.05$
10 × 16	3.2	0.7	1.2	5.0	$0.6 \pm 0.05$
10 × 20	3.2	0.7	1.2	5.0	$0.6 \pm 0.05$
12.5 × 20	3.2	0.7	1.2	5.0	$0.6 \pm 0.05$
12.5 × 25	3.2	0.7	1.2	5.0	$0.6 \pm 0.05$
16 × 20	3.5	0.7	1.6	7.5	$0.8 \pm 0.05$
16 × 25	3.5	0.7	1.6	7.5	$0.8 \pm 0.05$
16 × 31.5	3.5	0.7	1.6	7.5	$0.8 \pm 0.05$
16 × 35.5	3.5	0.7	1.6	7.5	$0.8 \pm 0.05$
16 × 40	3.5	0.7	1.6	7.5	$0.8 \pm 0.05$
18 × 20	3.5	0.7	1.6	7.5	$0.8 \pm 0.1$
18 × 25	3.5	0.7	1.6	7.5	$0.8 \pm 0.1$
18 × 31.5	3.5	0.7	1.6	7.5	$0.8 \pm 0.1$
18 × 35	3.5	0.7	1.6	7.5	$0.8 \pm 0.1$




**B41898**

**Very long useful life – 125 °C**

**Bent 90° leads for horizontal mounting pinning**

Last 3 digits of ordering code: 012




The series B41897 and B41898 have no sleeve nor minus pole marking, the positive pole is marked on the aluminum case side instead.

KAL1094-H-E

Case size d × l (mm)	Dimensions (mm)				
	C ±0.5	E ±0.5	F ±0.5	a ±0.5	Øb
16 × 20	4.0	4.0	12.0	7.5	0.8 ±0.05
16 × 25	4.0	4.0	12.0	7.5	0.8 ±0.05
16 × 31.5	4.0	4.0	12.0	7.5	0.8 ±0.05
16 × 35.5	4.0	4.0	12.0	7.5	0.8 ±0.05
16 × 40	4.0	4.0	13.0	7.5	0.8 ±0.05
18 × 20	4.0	4.0	13.0	7.5	0.8 ±0.1
18 × 25	4.0	4.0	13.0	7.5	0.8 ±0.1
18 × 31.5	4.0	4.0	13.0	7.5	0.8 ±0.1
18 × 35	4.0	4.0	13.0	7.5	0.8 ±0.1
18 × 40	4.0	4.0	13.0	7.5	0.8 ±0.1

Bent leads for diameter 12.5 mm available upon request.


**Packing units and box dimensions**
**Ammo pack**


Case size d × l mm	Dimensions (mm)			Packing units pcs.
	A <sub>max</sub>	B <sub>max</sub>	C <sub>max</sub>	
8 × 11.5	345	60	240	1000
10 × 12.5	345	60	280	750
10 × 16	345	65	200	500
10 × 20	345	65	200	500
12.5 × 20	345	65	260	500
12.5 × 25	345	70	260	500
16 × 20	325	65	285	300
16 × 25	325	65	285	300
16 × 31.5	325	80	275	300
18 × 20	325	65	285	250
18 × 25	325	65	285	250
18 × 31.5	325	80	275	250



**B41898**

**Very long useful life – 125 °C**

**Overview of packing units and code numbers**

Case size d × l  mm	Standard, bulk pcs.	Taped, Ammo pack pcs.	Kinked leads, bulk pcs.	Cut leads, bulk pcs.	PAPR				
					Crimped leads, blister pcs.	J leads, blister pcs.	Bent 90° leads, blister pcs.		
8 × 11.5	1000	1000	–	–	–	–			
10 × 12.5	1000	750	–	1000	–	900			
10 × 16	1000	500	–	1000	–	675			
10 × 20	500	500	500	500	–	500			
12.5 × 20	350	500	350	350	–	300	1)		
12.5 × 25	250	500	500	500	–	225	1)		
16 × 20	250	300	200	200	200	200	420		
16 × 25	250	300	200	200	216	216	216		
16 × 31.5	200	300	250	250	180	180	180		
16 × 35.5	100	–	100	100	150	150	150		
16 × 40	125	–	100	100	72	72	72		
18 × 20	175	250	175	175	200	200	420		
18 × 25	150	250	150	150	200	200	200		
18 × 31.5	100	250	100	100	150	150	150		
18 × 35	100	–	100	100	150	150	150		
18 × 40	125	–	100	100	72	–	72		
The last three digits of the complete ordering code state the lead configuration	<b>000</b>	Code	F (mm)	d (mm)	<b>001</b>	<b>002</b>	<b>003</b>	<b>004</b>	<b>012</b>
		<b>006</b>	3.5	8					
		<b>008</b>	5	8...12.5					
		<b>009</b>	7.5	16...18					

1) Available upon request



## Cautions and warnings

### Personal safety

The electrolytes used have been optimized both with a view to the intended application and with regard to health and environmental compatibility. They do not contain any solvents that are detrimental to health, e.g. dimethyl formamide (DMF) or dimethyl acetamide (DMAC). Furthermore, some of the high-voltage electrolytes used are self-extinguishing.

As far as possible, we do not use any dangerous chemicals or compounds to produce operating electrolytes, although in exceptional cases, such materials must be used in order to achieve specific physical and electrical properties because no alternative materials are currently known. We do, however, restrict the amount of dangerous materials used in our products to an absolute minimum.

Materials and chemicals used in our aluminum electrolytic capacitors are continuously adapted in compliance with the TDK Electronics Corporate Environmental Policy and the latest EU regulations and guidelines such as RoHS, REACH/SVHC, GADSL, and ELV.

MDS (Material Data Sheets) are available on our website for all types listed in the data book. MDS for customer specific capacitors are available upon request.

MSDS (Material Safety Data Sheets) are available for our electrolytes upon request.

Nevertheless, the following rules should be observed when handling aluminum electrolytic capacitors: No electrolyte should come into contact with eyes or skin. If electrolyte does come into contact with the skin, wash the affected areas immediately with running water. If the eyes are affected, rinse them for 10 minutes with plenty of water. If symptoms persist, seek medical treatment. Avoid inhaling electrolyte vapor or mists. Workplaces and other affected areas should be well ventilated. Clothing that has been contaminated by electrolyte must be changed and rinsed in water.



B41898

Very long useful life – 125 °C

## Product safety

The table below summarizes the safety instructions that must be observed without fail. A detailed description can be found in the relevant sections of separate file chapter "General technical information".

Topic	Safety information	Reference chapter "General technical information"
Polarity	Make sure that polar capacitors are connected with the right polarity.	1 "Basic construction of aluminum electrolytic capacitors"
Reverse voltage	Voltages of opposite polarity should be prevented by connecting a diode.	3.1.6 "Reverse voltage"
Mounting position of screw-terminal capacitors	Screw terminal capacitors must not be mounted with terminals facing down unless otherwise specified.	11.1. "Mounting positions of capacitors with screw terminals"
Robustness of terminals	The following maximum tightening torques must not be exceeded when connecting screw terminals: M5: 2.5 Nm M6: 4.0 Nm	11.3 "Mounting torques"
Mounting of single-ended capacitors	The internal structure of single-ended capacitors might be damaged if excessive force is applied to the lead wires. Avoid any compressive, tensile or flexural stress. Do not move the capacitor after soldering to PC board. Do not pick up the PC board by the soldered capacitor. Do not insert the capacitor on the PC board with a hole space different to the lead space specified.	11.4 "Mounting considerations for single-ended capacitors"
Soldering	Do not exceed the specified time or temperature limits during soldering.	11.5 "Soldering"
Soldering, cleaning agents	Do not allow halogenated hydrocarbons to come into contact with aluminum electrolytic capacitors.	11.6 "Cleaning agents"
Upper category temperature	Do not exceed the upper category temperature.	7.2 "Maximum permissible operating temperature"
Passive flammability	Avoid external energy, e.g. fire.	8.1 "Passive flammability"





Topic	Safety information	Reference chapter "General technical information"
Active flammability	Avoid overload of the capacitors.	8.2 "Active flammability"
Maintenance	Make periodic inspections of the capacitors. Before the inspection, make sure that the power supply is turned off and carefully discharge the capacitors. Do not apply excessive mechanical stress to the capacitor terminals when mounting.	10 "Maintenance"
Storage	Do not store capacitors at high temperatures or high humidity. Capacitors should be stored at +5 to +35 °C and a relative humidity of ≤ 75%.	7.3 "Shelf life and storage conditions"
		Reference chapter "Capacitors with screw terminals"
Breakdown strength of insulating sleeves	Do not damage the insulating sleeve, especially when ring clips are used for mounting.	"Screw terminals – accessories"

### Display of ordering codes for TDK Electronics products

The ordering code for one and the same product can be represented differently in data sheets, data books, other publications, on the company website, or in order-related documents such as shipping notes, order confirmations and product labels. The varying representations of the ordering codes are due to different processes employed and do not affect the specifications of the respective products.

Detailed information can be found on the Internet under [www.tdk-electronics.tdk.com/orderingcodes](http://www.tdk-electronics.tdk.com/orderingcodes).



**B41898**

**Very long useful life – 125 °C**

## Symbols and terms

Symbol	English	German
C	Capacitance	Kapazität
$C_R$	Rated capacitance	Nennkapazität
$C_S$	Series capacitance	Serienkapazität
$C_{S,T}$	Series capacitance at temperature T	Serienkapazität bei Temperatur T
$C_f$	Capacitance at frequency f	Kapazität bei Frequenz f
d	Case diameter, nominal dimension	Gehäusedurchmesser, Nennmaß
$d_{max}$	Maximum case diameter	Maximaler Gehäusedurchmesser
ESL	Self-inductance	Eigeninduktivität
ESR	Equivalent series resistance	Ersatzserienwiderstand
$ESR_f$	Equivalent series resistance at frequency f	Ersatzserienwiderstand bei Frequenz f
$ESR_T$	Equivalent series resistance at temperature T	Ersatzserienwiderstand bei Temperatur T
f	Frequency	Frequenz
I	Current	Strom
$I_{AC}$	Alternating current (ripple current)	Wechselstrom
$I_{AC,RMS}$	Root-mean-square value of alternating current	Wechselstrom, Effektivwert
$I_{AC,f}$	Ripple current at frequency f	Wechselstrom bei Frequenz f
$I_{AC,max}$	Maximum permissible ripple current	Maximal zulässiger Wechselstrom
$I_{AC,R}$	Rated ripple current	Nennwechselstrom
$I_{leak}$	Leakage current	Reststrom
$I_{leak,op}$	Operating leakage current	Betriebsreststrom
l	Case length, nominal dimension	Gehäuselänge, Nennmaß
$l_{max}$	Maximum case length (without terminals and mounting stud)	Maximale Gehäuselänge (ohne Anschlüsse und Gewindebolzen)
R	Resistance	Widerstand
$R_{ins}$	Insulation resistance	Isolationswiderstand
$R_{symm}$	Balancing resistance	Symmetrierwiderstand
T	Temperature	Temperatur
$\Delta T$	Temperature difference	Temperaturdifferenz
$T_A$	Ambient temperature	Umgebungstemperatur
$T_C$	Case temperature	Gehäusetemperatur
$T_B$	Capacitor base temperature	Temperatur des Gehäusebodens
t	Time	Zeit
$\Delta t$	Period	Zeitraum
$t_b$	Service life (operating hours)	Brauchbarkeitsdauer (Betriebszeit)



Symbol	English	German
V	Voltage	Spannung
V <sub>F</sub>	Forming voltage	Formierspannung
V <sub>op</sub>	Operating voltage	Betriebsspannung
V <sub>R</sub>	Rated voltage, DC voltage	Nennspannung, Gleichspannung
V <sub>S</sub>	Surge voltage	Spitzenspannung
X <sub>C</sub>	Capacitive reactance	Kapazitiver Blindwiderstand
X <sub>L</sub>	Inductive reactance	Induktiver Blindwiderstand
Z	Impedance	Scheinwiderstand
Z <sub>T</sub>	Impedance at temperature T	Scheinwiderstand bei Temperatur T
tan δ	Dissipation factor	Verlustfaktor
λ	Failure rate	Ausfallrate
ε <sub>0</sub>	Absolute permittivity	Elektrische Feldkonstante
ε <sub>r</sub>	Relative permittivity	Dielektrizitätszahl
ω	Angular velocity; 2 · π · f	Kreisfrequenz; 2 · π · f

**Note**

All dimensions are given in mm.

## Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, we are either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether a product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or lifesaving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet ([www.tdk-electronics.tdk.com/material](http://www.tdk-electronics.tdk.com/material)). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to our General Terms and Conditions of Supply**.

## Important notes

7. **Our manufacturing sites serving the automotive business apply the IATF 16949 standard.** The IATF certifications confirm our compliance with requirements regarding the quality management system in the automotive industry. Referring to customer requirements and customer specific requirements (“CSR”) TDK always has and will continue to have the policy of respecting individual agreements. Even if IATF 16949 may appear to support the acceptance of unilateral requirements, we hereby like to emphasize that **only requirements mutually agreed upon can and will be implemented in our Quality Management System.** For clarification purposes we like to point out that obligations from IATF 16949 shall only become legally binding if individually agreed upon.
8. The trade names EPCOS, CeraCharge, CeraDiode, CeraLink, CeraPad, CeraPlas, CSMP, CTVS, DeltaCap, DigiSiMic, ExoCore, FilterCap, FormFit, LeaXield, MiniBlue, MiniCell, MKD, MKK, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, PowerHap, PQSine, PQvar, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at [www.tdk-electronics.tdk.com/trademarks](http://www.tdk-electronics.tdk.com/trademarks).

Release 2018-10